# **DMSE-Q 2 Tools DME Station with Electric Pump**





The DME manages up to 4 tools simultaneously and is fully compatible with 10 different JBC tools. Check below for the complete list of compatible tools.

Rating: Not Rated Yet

Ask a question about this product

### Description

The MSE Electric Desoldering Module is indispensable for a complete desoldering process.

It provides the best soldering quality thanks to JBC Most Efficient Soldering System and additionally Sleep & Hibernation modes help to extend life of tips.

1 / 4

It features all the Excellence range benefits such as station customization, full control of soldering processes and remote work management.

The DMSE works simultaneously with the DR560 Desoldering Iron and the T245 Handle.

#### REFERENCES

DMSE-9QA

100 V

DMSE-1QA

120 V

DMSE-2QA

230 V

#### PRODUCT COMPOSITION

- 1

DME 4 Tools Control Unit

MSE-A Electric Desoldering Module for DDE & DME

T245-A General Purpose Handle (cartridge not included)

DR560-A Desoldering Iron

AD-SE Stand for T210 & T245 Handles

- 1 DR-SE Stand for DR560

CL8499 Manual Tip Cleaner

## SPECIFICATIONS DMSE-Q STATION

Selectable Temperature

90 to 450 °C / 190 to 840 °F

Vacuum

75% / 570 mmHg / 22.4 inHg
970 Hilling / 22-4 iling
Flow rate
9 SLPM
CONNECTIVITY
USB-B (rear)
Software PC / Traceability
USB-A (front)
Firmware update.
Soldering Graphics / Profiles management.
Dino-Lite USB microscope connection. Compatible models: AM2011 and AM2111.
Robot
RS-232 remote control or Smart Fume Extractor connection
LAN
Remote control / Traceability
Equipotential bonding
Optional connection to EPA
ESDIEOS
ESD safe
Tip to ground resistance
Tip to ground voltage
POWER SUPPLY
Peak power  160 W per tool – 23.5 V
Ambient operating temp. 10 to 50 ℃ / 50 to 120 ™
10 til 00 °C / 30 til 120 °F
DIMENSIONS AND WEIGHT
Control Unit
Control Unit 148 x 120 x 232 mm / 4.57 kg
5.8 x 4.7 x 9.1 in / 10.08 lb

## Reviews

There are yet no reviews for this product.

4 / 4