

HDE Heavy Duty Station



The HDE Station is the Most Powerful Soldering Unit of the JBC Range.

Rating: Not Rated Yet
[Ask a question about this product](#)

Description

It works with the JBC Most Efficient Soldering System and the Intelligent Sleep & Hibernation Modes.

This station comes with the comfortable T470-FA Handle and it is only compatible with C470 Cartridges.

It is also available a Heavy Duty Tweezers Set KHT470A that provides twice the power of the T470 Handle (it requires 2 HDE-U Control Units).

Soldering: HDE Heavy Duty Station

As all the JBC Stations, the HDE has a menu with more than 10 parameters to customize the control unit.

REFERENCES

HDE-9D

100 V

HDE-1D

120 V

HDE-2D

230 V

PRODUCT COMPOSITION

- 1 

- 1 

- 1 

- 1 

SPECIFICATIONS HDE STATION

Selectable Temperature

90 to 500 °C / 190 to 930 °F

CONNECTIVITY

USB-B (rear)

Software PC / Traceability

USB-A (front)

Firmware update Soldering Graphics management

Robot

RS-232 remote control or Smart Fume Extractor connection.

Equipotential bonding

Optional connection to EPA

Soldering: HDE Heavy Duty Station

ESD/EOS

ESD safe

Tip to ground resistance

Tip to ground voltage

5 mV RMS

POWER SUPPLY

Peak power

250 W - 42 V

Ambient operating temp.

10 to 50 °C / 50 to 120 °F

DIMENSIONS AND WEIGHT

Control Unit

148 x 120 x 232 mm / 2.80 kg

5.8 x 4.7 x 9.1 in / 6.17 lb

Package

368 x 474 x 195 mm / 6.23 kg

14.5 x 18.7 x 7.7 in / 13.73 lb

Reviews

There are yet no reviews for this product.