HDE Heavy Duty Station





The HDE Station is the Most Powerful Soldering Unit of the JBC Range.

Rating: Not Rated Yet

Ask a question about this product



It works with the JBC Most Efficient Soldering System and the Intelligent Sleep & Hibernation Modes

This station comes with the comfortable T470-FA Handle and it is only compatible with C470 Cartridges

It is also available a Heavy Duty Tweezers Set KHT470A that provides twice the power of the T470 Handle (it requires 2 HDE-U Control Units).

1 / 3

As all the JBC Stations, the HDE has a menu with more than 10 parameters to customize the control unit.

REFERENCES

HDE-9D

100 V

HDE-1D

120 V

HDE-2D

230 V

PRODUCT COMPOSITION



SPECIFICATIONS HDE STATION

Selectable Temperature

90 to 500 °C / 190 to 930 °F

CONNECTIVITY

USB-B (rear)

Software PC / Traceability

USB-A (front)

Firmware update Soldering Graphics management

Robot

RS-232 remote control or Smart Fume Extractor connection.

Equipotential bonding

Optional connection to EPA

ESD/EOS	
ESD safe	
Tip to ground resistance	
Tip to ground voltage	
5 mV RMS	
POWER SUPPLY	
Peak power	
250 W - 42 V	
Ambient operating temp.	
10 to 50 °C / 50 to 120 °F	
DIMENSIONS AND WEIGHT	
Control Unit	
148 x 120 x 232 mm / 2.80 kg	
5.8 x 4.7 x 9.1 in / 6.17 lb	
Package	
368 x 474 x 195 mm / 6.23 kg	
14.5 x 18.7 x 7.7 in / 13.73 lb	
Povious	

Reviews

There are yet no reviews for this product.