

NANO Stations - NASE2 Tools Nano Rework Station



The NASE Station is the Best Solution for Soldering and Rework of SMT Components Requiring the Highest Precision.

Rating: Not Rated Yet

[Ask a question about this product](#)

Description

It works with the JBC Most Efficient Soldering System and the Intelligent Hibernation Mode.

This station comes with the NT115-A Nano Handle and the AN115-A Adjustable Nano Tweezers. The short distance from the tip to the handle offers maximum control even when using a microscope.

The NASE-C Rework Station works with the C115 Cartridge Range.

As all the JBC Stations, the NANE has a menu with more than 10 parameters to customize the control unit.

REFERENCES

NASE-9C

100 V

NASE-1C

120 V

NASE-2C

230 V

PRODUCT COMPOSITION

- 1
NAE Control Unit

- 1


- 1


- 1


- 1


- 2


- 1


- 1


- 2


- 1


SPECIFICATIONS NASE STATION

Selectable Temperature

90 to 450 °C / 190 to 840 °F

CONNECTIVITY

Pedal (1 per tool)

Connect a pedal (ref.P-405) to control the tools. It allows using Nano tweezers for soldering.

USB-B (rear)

Software PC / Traceability

USB-A (front)

Firmware update Soldering Graphics management

Robot

RS-232 remote control or [RS-485 \(Modbus\)](#) connection.

Equipotential bonding

Optional connection to EPA

ESD/EOS

ESD safe

Tip to ground resistance

< 2 ohms

Tip to ground voltage

< 2 mV RMS

POWER SUPPLY

Peak power

14 W per tool – 8.5 V

Ambient operating temp.

10 to 50 °C / 50 to 120 °F

DIMENSIONS AND WEIGHT

Control Unit

170 x 90 x 135 mm / 2,50 kg

<div class="spec1 spec1tabla" style="box-sizing: border-box; float: left; margin-right: 3px; font-wei

Reviews

There are yet no reviews for this product.

