

NANO Stations - NANE 2 Tools Nano Soldering Station



The NANE Station is the Best Solution for Soldering and Rework of SMT Components Requiring the Highest precision. See Video for Soldering Examples.

Rating: Not Rated Yet

[Ask a question about this product](#)

Description

It works with the JBC Most Efficient Soldering System and the Intelligent Hibernation Mode.

This Station comes with Two NT115 Nano Handle. The Short Distance from the Tip to the Handle offers Maximum Control even when using a Microscope.

The NASE-C Rework Station Works with the C115 Cartridge Range.

As all the JBC Stations, the NANE has a menu with more than 10 parameters to customize the control unit.

REFERENCES

NANE-9C

100 V

NANE-1C

120 V

NANE-2C

230 V

PRODUCT COMPOSITION

- 1
NAE Control Unit

- 2


- 1


- 1


- 2


- 1


- 1


- 2


- 1


SPECIFICATIONS NANE STATION

Selectable Temperature

90 to 450 °C / 190 to 840 °F

CONNECTIVITY

Pedal (1 per tool)

Connect a pedal (ref.P-405) to control the tools. It allows using Nano tweezers for soldering.

USB-B (rear)

Software PC / Traceability

USB-A (front)

Firmware update Soldering Graphics management

Robot

RS-232 remote control or Smart Fume Extractor connection.

Equipotential bonding

Optional connection to EPA

ESD/EOS

ESD safe

Tip to ground resistance

< 2 ohms

Tip to ground voltage

< 2 mV RMS

POWER SUPPLY

Peak power

14 W per tool – 8.5 V

Ambient operating temp.

10 to 50 °C / 50 to 120 °F

DIMENSIONS AND WEIGHT

Control Unit

170 x 90 x 135 mm / 2.50 kg

6.7 x 3.5 x 5.3 in / 5.40 lb

Package

<div class="spec2 spec2tabla" style="border: 1px solid black; margin-bottom: 0px; margin-left: 202px; line-height: 1.2; padding: 2px 5px 2px 5px;"></div>

Reviews

There are yet no reviews for this product.