

CS Desoldering Station with Electric Pump



The CS Station is equipped with the MS-A Electric Pump and is ideal for desoldering the smallest plated through hole components and removing solder from surface mount pads.

Rating: Not Rated Yet
[Ask a question about this product](#)

Description

This Station comes with the comfortable DS360 Micro Desoldering Iron which uses the JBC exclusive Heating System and the intelligent Sleep & Hibernation features.

As all the Compact Stations, the CS has a menu with more than 10 parameters to customize the control unit.

REFERENCES

CS-9E

100 V

CS-1E

120 V

CS-2E

230 V

PRODUCT COMPOSITION

- 1
CS Control Unit

- 1


- 1


- 5


- 5


SPECIFICATIONS CS STATION

Selectable Temperature
180 to 450 °C / 360 to 840 °F

Vacuum
75% / 570 mmHg / 22.4 inHg

Flow rate
9 SLPM

CONNECTIVITY

USB-B
Software PC / Firmware update

Equipotential bonding
Optional connection to EPA

ESD/IEOS

Soldering: CS Desoldering Station with Electric Pump

ESD safe

Tip to ground resistance

POWER SUPPLY

Peak power

40 W - 23,5 V

Ambient operating temp.

10 to 50 °C / 50 to 120 °F

DIMENSIONS AND WEIGHT

Control Unit

150 x 175 x 145 mm / 4.0 kg

5.9 x 6.9 x 5.7 in / 8.82 lb

Package

495 x 295 x 255 mm / 5.47 kg

19.5 x 11.6 x 10 in / 12.06 lb

Reviews

There are yet no reviews for this product.