CS Desoldering Station with Electric Pump





The CS Station is equiped with the MS-A Electric Pump and is ideal for desoldering the smallest plated through hole components and removing solder from surface mount pads.

Rating: Not Rated Yet Ask a question about this product

Description	
This Station comes with the comfortable DS360 Micro Desoldering Iron which uses the JBC exclusive Heating System and the intelligent	Sleep & Hibernation feat

REFERENCES	
NEI ENENOEO	
CS-9E	
CS-1E	
120 V	
CS-2E 230 V	
PRODUCT COMPOSITION	
-1	
CS Control Unit	
-1	
-1	
-5	
-5	
SPECIFICATIONS CS STATION	
Selectable Temperature 180 to 450 °C / 380 to 840 °F	
Vacuum	
75% / 570 mmHg / 22.4 inHg	
Flow rate	
9 SLPM	
CONNECTIVITY	
USB-B Software PC / Firmware update	
Equipotential bonding	
Optional connection to EPA	
ESD/EOS	

ESD safe	
Tip to ground resistance	
POWER SUPPLY	
Peak power	
40 W - 23,5 V	
Ambient operating temp.	
10 to 50 °C / 50 to 120 °F	
DIMENSIONS AND WEIGHT	
Control Unit 150 x 175 x 145 mm / 4.0 kg	
100 A 170 A 140 Hill / 4.0 kg	
5.9 x 6.9 x 5.7 in / 8.82 lb	
Package	
495 x 295 x 255 mm / 5.47 kg	
19.5 x 11.6 x 10 in / 12.06 lb	
1000 0 1100 0 10 117 1200 0	

Reviews

There are yet no reviews for this product.