CA-Q Solder Feed Station



It is the ideal station for applications requiring a freehand like wire soldering to PCB, connectors or transformers and for intensive soldering of THT components.

Rating: Not Rated Yet Ask a question about this product

Description It provides the best solidering quality thanks to JBC Most Efficient Solidering System and additionally Sleep & Hibernation modes help to extend life of tips.

This Station comes with the AP250 Solder Feed Iron that works with C250 cartridges.

As all the Compact Stations, the CA has a menu with more than 10 parameters to customize the control unit.

REFERENCES

CA-9QE			
100 V			
CA-1QE			
120 V			
CA-2QE			

230 V

PRODUCT COMPOSITION

-1

CA Control Unit

SPECIFICATIONS CA-Q STATION

Selectable Temperature

90 to 450 °C / 190 to 840 °F

CONNECTIVITY

USB-B

Software PC / Firmware update

Equipotential bonding

Optional connection to EPA

ESD/EOS

ESD safe

Tip to ground resistance

Tip to ground voltage

POWER SUPPLY

Peak power 130 W - 23,5 V

Ambient operating temp. 10 to 50 °C / 50 to 120 °F

DIMENSIONS AND WEIGHT

Control Unit 150 x 175 x 145 mm / 2,67 kg

5.9 x 6.9 x 5.7 in / 5.88 lb

Package 234 x 234 x 258 mm / 3.15 kg

9.2 x 9.2 x 10.2 in / 6.94 lb

Reviews

There are yet no reviews for this product.