

CD-BQ General Purposes Station



It is the ideal soldering station for general electronic applications with a T245 Handle.

Rating: Not Rated Yet

[Ask a question about this product](#)

Description

It provides the best soldering quality thanks to JBC Most Efficient Soldering System and additionally Sleep & Hibernation modes help to extend life of tips.

Cartridge extractor facilitates fast and safe cartridge change of different tip geometries.

More than 200 cartridges of the C245 range of different geometries are available.

Soldering: CD-BQ General Purposes Station

As all the Compact Stations, the CD has a menu with more than 10 parameters to customize the control unit.

REFERENCES

CD-9BQE

100 V

CD-1BQE

120 V

CD-2BQE

230 V

PRODUCT COMPOSITION

- 1
CD Soldering Station

- 1


SPECIFICATIONS CD-BQ STATION

Selectable Temperature
90 to 450 °C / 190 to 840 °F

CONNECTIVITY

USB-B
Software PC / Firmware update

Equipotential bonding
Optional connection to EPA

ESD/EOS

ESD safe

Tip to ground resistance

Tip to ground voltage

Soldering: CD-BQ General Purposes Station

POWER SUPPLY

Peak power

130 W - 23,5 V

Ambient operating temp.

10 to 50 °C / 50 to 120 °F

DIMENSIONS AND WEIGHT

Control Unit

150 x 175 x 145 mm / 2,67 kg

5.9 x 6.9 x 5.7 in / 5.88 lb

Package

234 x 234 x 258 mm / 3.15 kg

9.2 x 9.2 x 10.2 in / 6.94 lb

Reviews

There are yet no reviews for this product.