

## DN-SE Stand for T210/T245/T470-NA



The sleep & hibernation mode automatically reduces the tip temperature when the tool is in the stand. As a result, a tip's life lasts up to 5 times longer.

Rating: Not Rated Yet  
[Ask a question about this product](#)

### Description

The MVE Pneumatic Desoldering Module is indispensable for a complete desoldering process. Clean and dry compressed air is required.

It provides the best soldering quality thanks to JBC Most Efficient Soldering System and additionally Sleep & Hibernation modes help to extend life of tips.

It features all the Excellence range benefits such as station customization, full control of soldering processes and remote work management.

Although the Control Unit is compatible with 10 different JBC tools, the DMPSE works simultaneously with the T210 Precision Purpose Handle, the T245 General Purpose Handle, the AM120 Micro Tweezers and the DR560 Desoldering Iron.

## REFERENCES

### DMPVE-9QA

100 V

### DMPVE-1QA

120 V

### DMPVE-2QA

230 V

## PRODUCT COMPOSITION

- 1

DME 4 Tools Control Unit

- 1

MVE-A Pneumatic Desoldering Module for DDE & DME

- 1

AM120-A Adjustable Micro Tweezers  
(cartridge not included)

- 1

T210-A Precision Purpose Handle  
(cartridge not included)

- 1

T245-A General Purpose Handle  
(cartridge not included)

- 1

DR560-A Desoldering Iron

- 2

AD-SE Stand for T210 & T245 Handles

- 1

AM-SA Stand for AM120 Micro Tweezers

- 1

DR-SE Stand for DR560

- 1

SCH-A Cartridge Holder

- 1

CL8499 Manual Tip Cleaner

## SPECIFICATIONS DMPVE-Q STATION

### Selectable Temperature

90 to 450 °C / 190 to 840 °F

### Vacuum (at 6 bar)

90% / 680 mmHg / 26.8 inHg

### Flow rate (at 6 bar)

15 SLPM

### Air pressure supply

up to 6 bar

## CONNECTIVITY

### USB-B (rear)

Software PC / Traceability

### USB-A (front)

Firmware update.

Soldering Graphics / Profiles management.

Dino-Lite USB microscope connection. Compatible models: AM2011 and AM2111.

### Robot

RS-232 remote control or Smart Fume Extractor connection

### LAN

Remote control / Traceability

### Equipotential bonding

Optional connection to EPA

### ESD/EOS

### ESD safe

Tip to ground resistance

Tip to ground voltage

## POWER SUPPLY

### Peak power

160 W per tool – 23.5 V

### Reviews

There are yet no reviews for this product.