

## TMT-9000S Soldering & Rework System



The TMT-9000S is based on Curie Heat Technology which responds to the thermal demands of each solder joint by adjusting the power instantaneously, thereby meeting the exact requirements of the substrate component and solder material.

Rating: Not Rated Yet

[Ask a question about this product](#)

### Description

- High thermal recovery & performance.
- 13.56MHz power supply with built-in LCD display.
- Dual switchable soldering ports.
- No calibration or operator training required.
- No additional coil assembly costs.

## TMT-9000S SPECIFICATIONS

Input Line Voltage:	TMT-9000PS-1	100-110 VAC
	TMT-9000PS-2	220-240 VAC
Tip to Ground Potential:	2mV, true RMS 50-500Hz	
Tip to Ground Resistance:	<2 Ohms DC	
Idle Temperature Stability:	±1.1°C (2°F)	
Ambient Operating Temperature:	10-40°C (50°F -104°F)	
Maximum Enclosure Temperature:	50°C (122°F)	
Fuse:	TMT-9000PS-1	125V 1A
	TMT-9000PS-2	250V 0.5A
Output Power (Maximum):	40 Watts	
Output Frequency:	13.56 MHz	
Size (W x H x D):	212.4mm x 118mm x 132mm	
Weight:	3.47 KG	
LCD display:	60.0mm x 16.0mm	
Input Line Frequency:	50/60 Hz	

## Reviews

There are yet no reviews for this product.